

Ultra low-power, weather-sealed flow meter cellular RTU



PULSE-OUTPUT FLOW  
METER MONITORING



INTERNAL 3G/4G  
MODEM OR  
SIGFOX RADIO



REMOTE DEVICE  
MANAGEMENT



LONG BATTERY LIFE

# N1

The Metermade® N1 Meter Interface Unit (MIU) is an ultra-low power device, designed to operate in the field for up to ten years on a single set of batteries (based on one report per day). It's housing meets the IP68 rating, permitting direct installation onto a flow meter and is capable of surviving submersion to a depth of four metres for four days.

The N1 is equipped with an internal 3G or 4G cellular module, capable of operating on the majority of cellular networks worldwide. It is approved for use on all Australian cellular networks. The N1 can be ordered with a Sigfox radio module instead of the cellular modem module, permitting use in the Sigfox RCZ4 network region.

The Metermade® N1 is the lowest cost option to provide highly reliable billing revenue data, directly to a host database using the industry standard DNP3 or FTP protocol. Remote configuration and device management is supported via leading industry SCADA applications, remote firmware download capability is provided via FTP file transfer.

The N1 is equipped with two (2) digital inputs and provides Forward/Reverse/Nett Totalisers and instantaneous flow calculation as standard. A 'magnetic swipe' function is provided to allow on-demand meter reads and data updates by field personnel.

The MIU configuration supports bulk editing/generation permitting high volume configuration and deployment.

# TECHNICAL SPECIFICATIONS

## General

Supply Voltage	3.5 – 8.5V DC, High-capacity, internal Lithium battery pack (field replaceable)
Current Draw	20 $\mu$ A sleep, 5 mA active, 200 mA 3G communications, 2 A (peak) 3G network detect, (measured at 3.6V DC)
Real Time Clock	Internal – Year, month, date, hour, minute, second, Automatic DNP3 time synchronisation from DNP3 master, Automatic cellular network time sync when using FTP data export mode
Temperature	-20°C to +65°C Celsius
Humidity	0 to 90% relative humidity, non-condensing
Programming	Windows based Configurator M+ configuration software, Remote device management via DNP3, Remote firmware download via FTP, local programming port
Mounting	90 mm (h) x 125 mm (d, nominal) / 155 mm (d, maximum), supplied with stainless steel mounting bracket
Environmental	NATA certified to IP68 (4 metres depth/4 days duration)

## IO Interfaces

Digital Input	2x low-current dry-contact binary inputs (non-isolated), each input supports pulse counting, up to 10Khz Forward/Reverse/Nett Totalisers with 32-bit rollover
System Input	Internal measurement of Cell Network RSSI, MIU temperature, MIU battery voltage and session status code

## Telemetry

3G Cellular (Standard)	Supports 3G B1 (2100), B5 (850), B8 (900), Class 3 output power (+24dBm)
4G Cellular (Option)	Supports 4G/LTE B1 (2100), B3 (1800), B5 (850), B8 (900), B28 (700), Class 3 output power (+23dBm)
Sigfox Radio (Option)	Sigfox compliant radio module, +22dBm TX power, RCZ4 region support covers Australia, New Zealand, Asia
Antenna	Internal antenna (2 dBi Gain)
SIM Card	1.8 and 3V UICC (Standard size SIM card)
Data Protocols	DNP3.0 Slave unsolicited / polled mode, FTP data export, Sigfox data export
Host Support	True TCP support to DNP host (supports three Master IP addresses)
Security	CHAP or PAP authentication, SIM credentials, configurable username, password and APN, built in IP firewall, 512-Bit AES Encrypted firmware download

## Approvals

Build	RoHs assembly
Standards	RCM (AUST/NZ), EMC compliance, other export standards on request
Production	Proudly Made in Australia

## Factory Accessories

Accessories	A comprehensive range of factory manufactured or sourced accessories to ensure reliable and swift solution deployment (see website)
-------------	---